



HG4930 MEMS INERTIAL MEASUREMENT UNIT

Honeywell

HG4930 MEMS INERTIAL MEASUREMENT UNIT



Proven - Dependable - Accurate

The HG4930 is a micro-electro-mechanical system (MEMS) based inertial measurement unit (IMU) designed to meet the needs of a range of applications across various markets including agriculture, AUVs, industrial equipment, robotics, survey/mapping, stabilized platforms, transportation, UAVs, and UGVs. With an industry standard communication interface, the HG4930 is easily integrated into the variety of architectures that these applications present. The extremely small size, light weight, and low power make the HG4930 ideal for most applications.

The HG4930 includes MEMS gyroscopes and accelerometers. In addition, the HG4930 employs an internal environmental isolation system to attenuate unwanted inputs commonly encountered in real world applications. The internal isolation and other proprietary design features ensure the HG4930 is rugged enough to meet the needs of the most demanding users.

Three different performance grades of the HG4930 are available as off-the-shelf items. Honeywell screens and calibrates all of the MEMS inertial sensors utilized in the HG4930 IMU.

The HG4930 is not ITAR controlled. Its Export Control Classification Number (ECCN) is 7A994.

KEY HONEYWELL ADVANTAGES

- World-class inertial sensor development, calibration and compensation.
- Proven reliability, dependability and ruggedness, throughout unit life.
- RS-422 Asynchronous or SDLC standard protocols.
- Highest performing MEMS IMU of its size and price.
- Smaller, lower-power and cost-effective replacement for a FOG.

HG4930 IMU TYPICAL KEY CHARACTERISTICS

Volume/Size	82 cm ³ (5in ³), 65 x 51 x 35.5 mm
Weight	140 grams (0.3 lbs)
Gyroscope Operating Range	-400°/s to +400°/s ³
Accelerometer Operating Range	-20 g to +20g
Supply Voltage	+5 VDC +/- 5%
Power Consumption	< 2 Watts
Operating Temperature Range	-54°C to +85°C
Data Type	Fully-Compensated Incremental/Delta Outputs are Ready for Integration into Position/Attitude
Gyro Bandwidth, -90°/-3 dB (Hz)	70/180
Accel Bandwidth, -90°/-3 dB (Hz)	70/180
Data Rates (Hz)	600 Hz / 100 Hz
Baud Rate	1 MBit

HG4930 IMU TYPICAL PERFORMANCE OVER FULL OPERATING TEMPERATURE RANGE

Marketing ¹ Part Number	Gyro Bias Repeatability (°/hr 1σ)	Gyro Bias In-run Stability ² (°/hr 1σ)	Gyro ARW (°/√hr)	Accel Bias Repeatability (mg 1σ)	Accel Bias In-run Stability (mg 1σ)	VRW (m/s/√hr)
HG4930CA51 HG4930CB50 ⁴	7	0.25	0.04	1.7	0.025	0.03
HG4930BA51	10	0.35	0.05	2.0	0.050	0.04
HG4930AA51	20	0.45	0.06	3.0	0.075	0.06

¹ When ordering direct from Honeywell, use part numbers 68904930-CA51, 68904930-BA51, 68904930-AA51 and 68904930-CB50.

² Gyro bias stability is >0.5 °/hr when measured over a constant operating period of one month.

³ Full performance to +/- 325%.

⁴ SDLC protocol. All others are asynchronous protocol.

For More Information

aerospace.honeywell.com/HGGuide

Honeywell Aerospace

2600 Ridgeway Parkway
Minneapolis MN 55413

N61-1523-000-012 | 10/19
© 2019 Honeywell International Inc.

THE
FUTURE
IS
WHAT
WE
MAKE IT

Honeywell