



SPECIFICATIONS

AVAILABLE RANGES: 75 K THRU 100 K LBS.
 EXCITATION: 10 VDC
 OUTPUT: 2 mV/V
 NONLINEARITY: ± .10% F.S.
 HYSTERESIS: ± .10% F.S.
 COMPENSATED TEMPERATURE: 60°F TO 160°F
 TEMPERATURE EFFECT:
 ZERO: .002% F.S./°F
 SPAN: .002% Rdg./°F
 BRIDGE RESISTANCE: 350 ohms
 MATERIAL: 17-4 PH SS

UNAMPLIFIED

PIN	DESIGNATION
A	(+) EXCITATION
B	(+) EXCITATION
C	(-) EXCITATION
D	(-) EXCITATION
E	(-) OUTPUT
F	(+) OUTPUT

REV	ECN
USED ON	060-1512-XX

A	REVISED PER ECN # 014	DRS	12/22/98	RAF	12/22/98
REV	DESCRIPTION	REVISED BY		APPROVED BY	
DRW:	DLE	CHK:	RAF	MFG:	ENG:
	8/29/80		12/22/98		RAF
SCALE:	SENSOTEC INC.				
NONE	2080 ARLINGATE LANE, COLUMBUS, OHIO 43228				
.X	© SENSOTEC, INC. ALL RIGHTS RESERVED				
±.1	ODD, MODEL 75				
.XX	9.0" O.D., 2 1/2-12 UN THREAD				
±.01	DOCUMENT NUMBER				
.XXX	000-1109-00				
±.005	63	SHEET 1 OF 1			
±1/2"					