



AVAILABLE CAPACITY: 75,000; 100,000 LBS.  
 OUTPUT: 2 mV/V NOMINAL  
 POSITIVE IN TENSION  
 ZERO BALANCE:  $\pm 1\%$  F.S.  
 NONLINEARITY:  $\pm 0.2\%$  F.S.  
 HYSTERESIS:  $\pm 0.2\%$  F.S.  
 SPAN T.C.:  $\pm 0.005\%$  Rdg./ $^{\circ}$ F  
 ZERO T.C.:  $\pm 0.005\%$  F.S./ $^{\circ}$ F  
 BRIDGE RESISTANCE: 350 OHM  
 EXCITATION: 10 VDC  
 MATERIAL: 17-4 P.H.  
 STAINLESS STEEL

WIRING CODE

PIN	DESIGNATION
A	(+)EXCITATION
B	(+)EXCITATION
C	(-)EXCITATION
D	(-)EXCITATION
E	(-)OUTPUT
F	(+)OUTPUT

SENSOTEC PART NUMBER: 060-5349-00

A	01-185: CHANGED ORIENTATION	RUG	JWD	JHM
REV	DESCRIPTION	REVISED BY	APPROVED BY	
DRW: JB	CHK: JP	MFG:	ENG: RJS	1/11/95
1/11/95	1/11/95			

SCALE: NONE	<b>SENSOTEC INC.</b> 2080 ARLINGATE LANE, COLUMBUS, OHIO 43228 © SENSOTEC, INC. ALL RIGHTS RESERVED	OUTLINE DRAWING, MODEL RM LOAD CELL STANDARD PRODUCT, $\phi 3.50$	DOCUMENT NUMBER
.X $\pm .1$			000-2935-00
.XX $\pm .01$			
.XXX $\pm .005$			
USED ON	63	SHEET 1 OF 1	

REV	
ECN	
USED ON	